



260-8® & 260-8P® Analog VOM

When a digital multimeter won't do.

Professionals have long recognized that a Simpson 260 analog meter does many things that even the best DMM cannot do...or cannot do as well, such as monitoring fluctuating trends and rates.

The 260-8 has even more features than you've come to expect from its predecessors. Standard and high energy fusing in conjunction with diodes network meter movement protection makes the 260-8 the best combination of quality and affordability.

The 260-8P has an additional relay overload protection circuit that is resettable and also provides audible continuity checking.

- **36 Measurement Ranges**- Covering both AC and DC Voltage and Current measurements, as well as Resistance testing
- **Connections Safeguarded**- Standard size reverse/recessed safety jacks prevent operator and/or tool contact with electrical connections of the instrument
- **Overload Protection**- Diode network protects instrument from overload damage during use (260-8P only)
- **Rugged Construction**- The Phenolic case is designed with heavy reinforced walls for maximum durability; self-shielding taut-band provides added shock resistance for the meter movement

Specifications

DC VOLTAGE

Ranges	Accuracy	Sensitivity
250mV, 1V, 2.5V, 10V, 25V, 50V, 250V, 500V, 1000V	2% of full scale	20K Ω per volt

AC VOLTAGE

Ranges	Accuracy	Sensitivity
2.5V, 10V, 25V, 50V, 250V, 500V, 1000V	3% of full scale	5K Ω per volt

AC CURRENT

Ranges: Up to 250 amperes with AC Amp-Clamp Adapter Accessory #00545

DECIBEL

5 Ranges: -20 to +50dB

Reference: 0dB= 1mW into 600 Ω

Ordering Information

ANALOG MULTIMETERS	Catalog No.	ACCESSORIES	Catalog No.	ACCESSORIES	Catalog No.
260-8, General Purpose	12388	Model 150-2 Amp-Clamp Adapter	00545	Case, Yellow Padded Nylon	00832
260-8P, Relay Protected	12391	Universal Kit, 14-Piece	05577	Case, Black Padded Nylon	00834
260-8RT, Roll Top Case	12389	Universal Kit, Deluxe 23-Piece	00818	Roll-Top Case	00248
260-8PRT, Protected, Roll Top Case	12392	Probe Set, threaded w/clips	00043	Case, Hard Leatherette Front Load	00805
		Model 151-2 Line Splitter (for 150-2)		Case, Molded Plastic	45028
		00544		Additional accessories are on pages 25-28.	



- **Portable, for the Workshop, Lab, or in the Field**- Portable enough to take with you, with benchtop accuracy.
- **Versatile**- Full-size test leads with threaded probe tips for screw-on alligator clips and versatility. Eliminates the need to change test leads while working
- **Reverse Banana Jacks for Safety**
- **Simple Operation**- Two knobs control the selection of ranges and functions

DC CURRENT

Ranges	Accuracy	Voltage Drop: (Nominal)
50 μ A, 1mA, 10mA, 100mA, 500mA, 10A	1.5% full scale 50 μ A 2.0% of full scale, all other	250mV on 50 μ A, 1mA; 255mV on 10mA, 10A; 300mV on 100mA; 500mV on 500mA

RESISTANCE

Ranges	Accuracy	Max. Indication
Rx 1 Rx 100 Rx 10K	2.5° of arc on Rx1 2.0° of arc on other	0-2K Ω 0-200K Ω 0-20M Ω

RATED CIRCUIT-TO-GROUND VOLTAGE: 1000V (AC or DC) max.

FUSE: F1 1A, 250V, type 3AG, quick acting Littelfuse® Type 312001; F2 2A, 600V Littelfuse® Type BLS or 2A 600V, Bussman® Type BBS.

BATTERIES: 1.5V AA, 9V (Neda No. 13F, 1604A)

PHYSICAL: Dimensions 7"(H)x5.5"(W)x3.1"(D), (18x14x8cm) Weight 3lbs. (1.4Kg)
Specifications subject to change without notice.